

# Specification Sheet

Purity: >95%, APS: 10 nm

Stock No: NS6130-04-448, CAS: N/A

<b>Product</b>	:	<b>Quick Drying Enamel</b>
Stock No	:	NS6130-04-448
Product Brand	:	Supreme
APS	:	10 nm
Purity	:	>95%
Color	:	Black
Density	:	1.09 Kg/Litre
Viscosity	:	450 - 500 Cpu
Finish	:	Full Gloss
Mwcnt Wt%	:	2.950 – 3.010 Wt%
Vehicle Type	:	Styrenated Alkyd
Pigment Type	:	Inorganic Oxides & Chromates
Solvent Type	:	Aromatic Hydrocarbons
Flash Point Min	:	22°C
Drying Time: Surface	:	10 – 15 Minutes
Hard	:	1 – 2 Hours
Application Method	:	Spray Or Dip
Application Viscosity	:	Conventional Spray: 18 – 20” Fc4
Recommended Thinner	:	Q.D Enamel Thinners
Fineness of Grind	:	5 Microns
Gloss	:	85% On 60°
Heat Resistance	:	250 – 300 Degrees C
Coverage At Dft 40 µm	:	8 Square Metres Per Litre
Dry Film Thickness	:	40 Microns (Recommended)
Shelf Life	:	6 – 12 Months

**Intelligent Materials Pvt. Ltd.**

www.nanoshel.com, sales@nanoshel.com

Storage

:

Store Away From Direct Heat

**Main Inspect Verifier**

:

**Manager QC**



**Note:** Product Specification are subject to amendment and may change over time



---

**NANOSHEL LLC** *(In Collaboration)*

3422 Old Capitol Trial Suit 1305, Wilmington DE - 19808 USA  
(001) 302 652-3464, + 91 9779-880077